

E-USR/P CE-50/S


**Slip Rings for
Wrapping Machines**

CONDUCTIX
wipac

E-USR/P

f o r

Rotating Arm Wrapping Machines



Construction & Design

E-USR/P

- Free inner hole 42 mm
- Side opening for full access
- Standard Hub for fixation
(variant M48x1.5 & Terminal Board)
- Captive screws for cover closure
- Voltage: 690V
- IP Protection: IP51




Standard composition:

6|12|18|24|30|36 poles “type A*”
(others on request)

Rings wiring:

- (A) Axial flying leads
- (B) Radial flying leads
- (C) Terminal board

*9 A - Current in rotation T = 30° C, S1



Few screws – full side opening

- Easy wiring, installation and inspection

Captive screws

- No risk to lose screws on-site
- Electrical Safety

Brush Holders removable

individually

- No tools
- Easy inspection and maintenance

Modular Design

- same design for all current variants

Easy Replacement

- individually mountable and dismantable

- 1 **Top Plate** | Material: Polyamide 12 (PA12)
With anti-rotating rods and holes for cable glands integrated
- 2 **Housing** | Material: Polyamide 12 (PA12)
Modular side modules for fast opening and full access
- 3 **Slip Ring** | New European range USR
- 4 **Installation** | Several variants (flying leads, terminal board, threaded M48x1,5 hub)

CE-50/S

f o r

Rotating Table Wrapping Machines



Construction & Design

CE-50/S

- **External diameter** 180 mm
- **Side opening for full access**
- **Captive screws** for cover closure
- **Integrated Air Joint size 1/4"**
for the transfer to the rotating platform
of air used by pneumatic valves
- **Voltage: 400 V**
- **IP Protection: IP54**

Standard composition:

18|22|26|30 poles "type 11*"
(others on request)



Few screws – full side opening


- Easy wiring, installation
and inspection

Captive screws

- No risk to lose screws on-site
- Electrical Safety

Fluidic Joint 1/4" integrated

- in end-plate
- Easy hose installation
- Compact dimensions



Modular Design

- same design for
all current variants

Easy Replacement

- individually mountable
and dismantlable

- 1 **End Plate** | Material:
Polyamide 12 (PA12)
- 2 **Housing** | Material:
Polyamide 12 (PA12)
Modular side modules for
fast opening and full access
(metal enclosure available)
- 3 **Wiring** | Standard
2 m only on rings
- 4 **Air Joint** | Size 1/4"
- 5 **Installation** | Standard
flange

*10 A - Current in rotation T = 30° C, S1

www.conductix.com

Conductix-Wampfler has just one critical mission:

To provide you with energy and data transmission systems that will keep your operations up and running 24/7/365.

To contact your nearest sales office, please refer to:

www.conductix.contact

